

FEATURES

Western Filter suction strainers are constructed with aluminum end-caps and stainless steel screen to protect hydraulic pumps from harmful large contaminants that tend to accumulate on the bottom of hydraulic reservoirs.

- 5 Sizes of NPTF threads available
- Available with or without bypass
- Replaces competitive products

Sizing Data	Nominal Capacity (GPM*)	(L) Inches	(D) Inches	(L) MM	(D) MM
3/4" NUT	8	4.1	2.7	105	68
1" NUT	10	5.5	2.7	139	68
1-1/4" NUT	20	7.7	3.5	195	88
1-1/2" NUT	50	10.0	3.5	260	88
3" NUT	100	10.7	5.7	272	150

*Flows indicated =/ < 1.0 PSID maximum @ 150 SSU

Model Number	Size	Micron Rating	Bypass
WSS-8-125-	3/4" NPT	125 (standard)	NON-BYPASS ADD - N AT END OF MODEL # (i.e. - WSS-8-125-N)
WSS-8-060-	3/4" NPT	060 (special order)	
WSS-8-250-	3/4" NPT	250 (special order)	
WSS-10-125-	1" NPT	125 (standard)	3 PSID BYPASS ADD - X AT END OF MODEL # (i.e. - WSS-8-125-X)
WSS-10-060-	1" NPT	060 (special order)	
WSS-10-250-	1" NPT	250 (special order)	
WSS-20-125-	1-1/4" NPT	125 (standard)	
WSS-20-060-	1-1/4" NPT	060 (special order)	
WSS-20-250-	1-1/4" NPT	250 (special order)	
WSS-50-125-	1-1/2" NPT	125 (standard)	
WSS-50-060-	1-1/2" NPT	060 (special order)	
WSS-50-250-	1-1/2" NPT	250 (special order)	
WSS-100-125-	3" NPT	125 (standard)	
WSS-100-060-	3" NPT	060 (special order)	
WSS-100-250-	3" NPT	250 (special order)	

WSS Series

In-Tank Suction Strainers

